PREFACE

This document supersedes the South Florida Water Management District (SFWMD) Technical Publication 84-3 entitled "South Florida Water Management Documentation Report" which was released in February 1984. The main text is divided into three parts: Model Overview, Functional Specifications, and Miscellaneous Topics. There are 11 accompanying appendices.

The model overview is presented in the first chapter where a general description of the South Florida Water Management Model (SFWMM) is given. A short introduction to the model is followed by a history of its evolution from the 1970s to the present. The model is defined further in terms of its spatial extent and discretization, time discretization, and hardware requirements. Although the model is referred to as a hydrologic simulation model, it goes beyond simulating the components of the hydrologic cycle. In fact, the majority of the code written for the model deals with the complex operational and management aspects of the existing and proposed hydraulic infrastructure in the modeled area. A flowchart of the general logic in the model is presented.

Functional specifications refer to the discussion of the algorithms employed in both the hydrologic and management components of the model. Hydrologic processes such as rainfall, evapotranspiration, overland flow, subsurface flow and canal routing are discussed in Chapter 2. Chapter 3 deals with the operational aspects of the extensive system of canals, structures and pump stations that form the Central and Southern Florida Project for Flood Control and Other Purposes. The material is presented by geographical area. The different operating policies that apply in each area, together with their corresponding model implementations, are explained.

Miscellaneous topics covered in Chapters 4 through 6 include calibration, sensitivity analysis and uncertainty analysis. Model calibration is used to reinforce the model's predictive capability by showing how well the simulated stage and discharge values match historical data. Results from a sensitivity analysis, expressed as correlation of model input parameter and model output, can be used as a guide during model calibration and as a tool for establishing priorities in future data collection activities. Uncertainty analysis provides the modeler and/or the decision-maker with confidence limits that express the variation in model output as a function of assumed confidence limits on the model input parameters.

The intent and purpose of this document require some clarifications. The model is constantly being improved. It is almost certain that any form of model documentation is outdated, in one way or another, at the time of its release. The reader should, therefore, be aware that the discussions in the following chapters pertain to version 3.5 of the model unless, otherwise, noted. Updates to this documentation may come in several forms: technical notes, memoranda or reports in printed and/or electronic format. An Internet WEB page version is also available.

The South Florida Water Management Model is the most detailed, physically-based simulation model that combines the hydrology and management aspects of a greater portion of the South Florida Water Management District. Several man-years of dedicated work were required to achieve the current status of the model. The model is regional in spatial extent because it covers a

large area of substantial heterogeneity in both natural and managed hydrology. A 2-mile by 2-mile fixed resolution grid system makes the model large-scale. The SFWMM is a coupled surface water-groundwater model which incorporates overland flow, canal routing, unsaturated zone accounting and two-dimensional single layer aquifer flow. The model is site-specific because it was exclusively developed for the South Florida region. Expansion of the model boundaries will require data and source code modifications depending on the hydrology and corresponding management of any new areas to be included.

In addition to simulating the natural hydrology in South Florida, the model also simulates the management processes that satisfy policy-based rules (both existing and proposed) to meet flood control, water supply and environmental needs. The model runs on a daily continuous simulation mode, instead of event-based, for 31 years (1965-1995 period-of-record). Using this type of distributed hydrologic modeling requires enormous computing power. The model has performed well in various applications using SunWorkstationsTM running under the UNIXTM operating system. Prior to the current hardware/operating system configuration, the complexity and detail of the hydrology and hydraulics simulated by the model had been very limited. The algorithms had to be simple and able to accommodate limited available data in order to complete a model run within a reasonable amount of computer time. Current model applications require from six to ten hours of run time on SunWorkstationsTM. As of this writing, no plans have been made to make the model work across different platforms, e.g., VAXTM OS, MacTM OS and WindowsTM.

Finally, this document is a primer to the SFWMM. It is not intended to be a user's or programmer's manual. It should be used as a reference guide to the structure and algorithms of the model. Proficiency with the use of the model itself cannot be gained merely by reading this document. Extensive training is necessary to effectively define a problem, formulate a scenario, prepare input files, run the model, analyze the results and make sound recommendations. Running the model and interpreting the results without prior knowledge of the system are not recommended. The model domain encompasses a complex natural and managed hydrologic system and the system components are highly interdependent. Local changes within the regional system can have far-reaching impacts on the hydrology at other locations within the system. Evaluation of the impacts of proposed changes to the regional system is a complex and challenging task -- one that requires a thorough understanding and knowledge of the entire modeling domain. This documentation was prepared with a broad audience base in mind. The complexity of the system, and limited time and manpower preclude the inclusion of a user-friendly interface. Likewise, all of the possible detailed questions about the internal workings of the model are not addressed. Attempting to do so would require a similar amount of resources as were needed to develop and improve the model. Additional information regarding details of the model can be obtained from the SFWMD staff responsible for the continual development and application of the South Florida Water Management Model.

Lehar M. Brion, Everett R. Santee, Calvin J. Neidrauer, Paul J. Trimble and Narayanan C. Krishnan

HSM Division, Planning Department, SFWMD West Palm Beach, FL April 1999

ABBREVIATIONS

ac-ft acre-feet

AFSIRS Agricultural Field -Scale Irrigation Requirements Simulation Model

ASCII American Standard Code for Information Interchange

ASR Aguifer Storage and Recovery or Aguifer Storage and Retrieval

BCNP Big Cypress National Preserve
BMP Best Management Practice
cfs or ft³/s cubic feet per second

Corps U.S. Army Corps of Engineers (same as USACE, ACOE or COE)

C&SF Project Central and South Florida Flood Control Project

District South Florida Water Management District (same as SFWMD)

DSS Hydrologic Engineering Center's Data Storage System (same as HECDSS)

EAA Everglades Agricultural Area ENP Everglades National Park

ENR Project Everglades Nutrient Removal Project

EPA Everglades Protection Area

ET evapotranspiration

FAO Food and Agriculture Organization

FGFWFC Florida Game and Freshwater Fish Commission

ft feet

GIS Geographical Information System

HECDSS Hydrologic Engineering Center's Data Storage System (same as DSS)

in. inches lb pounds

LEC Lower East Coast

LECSA Lower East Coast Service Area

LECRWSP Lower East Coast Regional Water Supply Plan

LOK Lake Okeechobee

LOSA Lake Okeechobee Service Area LWDD Lake Worth Drainage District

MGD million gallons per day

mi miles

NESRS Northeast Shark River Slough NGVD National Geodetic Vertical Datum

NOAA National Oceanographic and Atmospheric Administration

NSM Natural System Model PDE Partial Differential Equation

Restudy C&SF Project Comprehensive Review Study

SCS Soil Conservation Service
SCCS Source Code Control System
SDCS South Dade Conveyance System

sec seconds

SRS Shark River Slough

SFRSM South Florida Regional Simulation Model

SFWMD South Florida Water Management District (same as District)

SFWMM South Florida Water Management Model

SSM Supply-Side Management STA Stormwater Treatment Area

sq mi square miles

SWIM Plan Surface Water Improvement and Management Plan

USACE U.S. Army Corps of Engineers (same as Corps, ACOE or COE)

USFWS U.S. Fish and Wildlife Service

USGS U.S. Geological Survey WCA Water Conservation Area